



SILTECH LLC
2170 Luke Edwards Road
Dacula, Ga 30019
(678)442-0210 (Tel) (678)442-9624 (Fax)

TECHNICAL DATA SHEET

Silsurf® B-2010

DESCRIPTION

Silsurf® B-2010 is a water-insoluble silicone surfactant. The HLB is 4.5, producing water in oil emulsions.

The INCI name for **Silsurf® B-2010** is PEG-10 dimethicone.

TYPICAL PROPERTIES

Appearance	Clear liquid
Color, Gardner	1
Active Content %	100
Viscosity at 25 ⁰ C, cps	600
Specific Gravity at 25 ⁰ C	1.01
Refractive Index	1.42

USES & APPLICATIONS

Silsurf® B-2010 an excellent water-in-oil emulsifier.

The recommended concentration used is between 1.0-5.0% weight percent of the total formulation.

SAFETY

Before handling, read the Material Safety Data Sheet and container label for safe use, physical and health hazard information.

STORAGE AND SHELF LIFE

When stored below 20⁰C, **Silsurf® B-2010** has a shelf life of 24 months from the date of shipment.

PACKAGING

Silsurf® B-2010 is supplied in 20kg pails and 200kg drums

DISCLAIMER

Siltech believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Siltech, however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.

SILTECH® SILQUAT® FLUROSIL® SILSURF® SILUBE® SILWAX® are registered trademark of Siltech LLC, Dacula, Ga.